



CANOVA

- Linea arrotondata priva di spigoli e viti a vista.
- Perno di scorrimento, cromato rettificato e lappato.
- Boccole di scorrimento autolubrificanti.
- Paracolpi su carrello in gomma vulcanizzata.
- Coperchio supporto vela smontabile.
- Parafetta in acciaio inox con incastro a baionetta.
- Tutte le minuterie acciaio inox.
- Sistema di tenuta stagna su puleggia.
- 41 mm di distanza fra lama e corpo macchina.
- Copertura inferiore.
- Scheda elettronica commutabile 110-220V monofase o 220-380V trifase.
- Affilatoio con vaschetta inferiore di protezione.
- Estrattore lama di serie versione 300.
- Inclinazione lama 38°.

- *Rounded design and no sharp edges and visible screws.*
- *Chrome plated ground and lapped slide rod.*
- *Self lubricating slide rod bushings.*
- *Vulcanized rubber stops on carriage.*
- *Removable support cover for thickness gauge plate.*
- *Stainless steel slice deflector with bayonet fitting*
- *Stainless steel screws and fittings.*
- *Enclosed and sealed belt pulley.*
- *41 mm distance between blade and motor.*
- *Bottom cover.*
- *Changeover electronic circuit 110-220V single or 220-280V three phase.*
- *Built in sharpening tool with bottom protection.*
- *Standard Blade Removal Tool (BRT) for 300 ver.*
- *38° blade inclination.*

CANOVA

- Manopole plastica / Piedini in gomma / Interruttore isolato IP 44

CANOVA TOP

- Manopola alluminio / Piedini in alluminio telescopici con base in gomma / Pulsanti IP 67 in acciaio inox.

CANOVA

- Plastic knob. / Rubber feet. / Switch with IP44 protection rating.

CANOVA TOP

- Aluminium knob. / Aluminium telescopic feet with rubber base / Stainless steel pushbuttons with IP67 protection rating.






CANOVA 300 TOP



Ampio spazio tra lama e corpo macchina
More space between blade and body machine



Spazioso piano per appoggio prodotto
Large tray



★ Canova 250	250/10"	147/0,20	19	275	240x230	428	290	560	495	365	660	500	550	230	140	190	175	24.5	800x600x520	27
★ Canova 275	275/11"	210/0,29	19	275	240x230	428	290	580	495	360	650	495	530	230	155	208	185	25.5	800x600x520	28
★ Canova 300	300/12"	210/0,29	19	275	250x275	428	290	590	495	355	640	495	515	260	175	223	207	26.5	800x600x520	29

★ TOP



CANOVA 250



CANOVA 250 TOP



CANOVA 300